

GTJZ SERIES

Product Advantages

- *Large angle steering system
- Disc brake system
- Intelligent charging system
- Overload protection
- •Self-diagnostic function
- Level alarm system
- Infinitely variable speed





STANDARD CONFIGURATION

- 2-Wheel Hydraulic Drive
- 2-Wheel Steering
- High/Low travel speed
- Extension Platform
- Foldable Guardrails
- Tilt sensing Alarm
- Down Alarm
- Safety Support
- Timer
- Intelligent Charger
- Swing-out Tray
- Pothole Protection Device
- Emergency Down Device
- Emergency Release Brake

OPTIONAL DEVICES

Electric Drive

MODEL		GTJZ06	GTJZ08	GTJZ10	GTJZ12	GTJZ14
Max platform height(m)		5.8	8.1	10.2	11.95	13.75
Max working height(m)		7.8	10.1	12.2	13.95	15.75
Platform Extension(m) G		0.9	0.9	0.9	0.9	0.9
Lift capacity/extension deck(kg)		230/110	230/110	320/110	320/110	230/110
Grade-ability		25%	25%	25%	25%	25%
Max. allowable slope(°)		2/3	2/3	2/3	2/3	2/3
Turing radius Minimum(m)		2.1	2.2	2.2	2.2	2.6
Travel speed(stowed) (km/h)		3.5	3.5	3.6	3.6	3.6
Up/Down Speed (m/s)		0.18-0.25	0.18-0.25	0.18-0.25	0.18-0.25	0.18-0.25
Length /Width(stowed) (m)	D/F	1.82×0.76	2.48×1.15	2.48×1.15	2.48×1.15	2.83×1.25
Height(Rails up/Rails down) (m)	C/E	2.2/1.84	2.32/1.82	2.45/1.95	2.57/2.07	2.61/2.1
Platform Size(Lengh/With) (m)	A/B	1.65×0.75	2.32×1.13	2.32×1.13	2.32×1.13	2.68×1.13
Ground Clearance (m)		0.1/0.02	0.1/0.02	0.1/0.02	0.1/0.02	0.1/0.02
Tyres(m)		0.305×0.118	0.381×0.127	0.381×0.127	0.381×0.127	0.381×0.127
Weight(kg)		1500	2450	2710	2880	3150
Lift motor (V/kw)		24/3.0	24/4.5	24/4.5	24/4.5	24/4.5
Battey(V/ah)		4×6/225	4×6/225	4×6/240	4×12/300	4×12/300
Charge(V/a)		24/30	24/30	24/30	24/30	24/30







Main Configuration for electrical scissor platform



Electric Motor & Hydraulic pump from Bucher



Valve from Hydraforce



Brake & Driving motor from White



Brake release valve from White



Joystick and Controller from Delta



Electric motor's controller from Curtis



Battery from Trojan; Charge from Longsheng